

Spektra Controller

RGBW Lighting control



Product Overview



Specifications

| | |
|-----------------------|--|
| Input | 12V/24V DC |
| Wattage | 30W |
| Application | LED strip lighting (12V/DC) |
| Operating Temperature | 0 °C ~ 40 °C 10% ~90% RH |
| Storage Temperature | -10 °C ~ -70 °C 5% ~90% RH |
| Pairing | <ul style="list-style-type: none"> • Silux Control® network • Direct connect • Software teach available |
| Network | Silux Control® RF proprietary encrypted |
| Radio Range | 50m open air & meshing up to 1km |
| Encryption | Silux Control® RF proprietary meshing |
| Language | English, others coming soon |
| OS | Android 4.0+, iOS 8.0+, Windows 7+ |
| App Software | Silux Control® can be integrated with other automation features of Silux Control® |

The Spektra® Controller connects to LED RGBW strip lighting giving you the ability to change colors, set schedules, set sunrise or sunset routines and many more.

Features:

- Sunrise & Sunset optional
- Full Color Spectrum
- User defined
- Plug-In control unit
- Dimmable via the Silux Control® app software
- No need for a Silux Collector®
- Silux Color Stepping
- Silux Color Rainbow

| | | | |
|----------------------------------|--|--|--|
| <p>Works cooperatively with:</p> | | | |
| | | | |